

# NOTIFICATION OF AIRCRAFT TYPE ELIGIBLE FOR OPERATION

# UNDER THE PROVISIONS OF CIVIL AVIATION ORDERS SECTION 95.32

## NUMBER AD32-6 ISSUE 3

AIRCRAFT MANUFACTURER:

AIRBORNE WINDSPORTS PTY. LTD.

UNIT 22/30 KALAROO ROAD

REDHEAD NSW 2290

AIRCRAFT TYPE:

EDGE X 503 BASE FITTED WITH WIZARD WING

SPECIFICATION:

SEE DATA SHEET DS32-6 issue 3 DATED 7/8/2002 OR

LATER ISSUE.

THE AIRCRAFT TYPE DEFINED BY:

AIRBORNE WINDSPORTS EDGE DRAWING LIST, ISSUE 4.1 (Report 97/32/DS), AND

DRAWING LIST ISSUE 4.0, (Report 97/24/DS), PLUS

DRAWING LIST WIZARD WING ISSUE 1 (Report 97/27/DS), IS ELIGIBLE FOR OPERATION UNDER THE PROVISIONS OF CIVIL AVIATION ORDERS SECTION 95.32 ISSUE 1 IN ACCORDANCE WITH PARAGRAPH 1.1(f)(ii) AND AIRBORNE WINDSPORTS AIRWORTHINESS CONDITIONS AS APPROVED 30 MARCH 1990.

SIGNED:

DATE: 7/8/2002

I. KEARSLEY for and on behalf of CASA

#### CIVIL AVIATION AUTHORITY AUSTRALIA

### CIVIL AVIATION ORDER SECTION 95.32 AIRCRAFT DATA SHEET

### NUMBER AD 32-6 ISSUE 3

AIRCRAFT MANUFACTURER:

AIRBORNE WINDSPORTS PTY. LTD.

UNIT 22/30 KALAROO ROAD

REDHEAD NSW 2290

AIRCRAFT TYPE:

EDGE X 503 FITTED WITH WIZARD WING

ENGINE:

ROTAX 503

**ENGINE LIMITS:** 

6800 R.P.M. MAXIMUM (49.6 HP @ 6500 RPM)

**GEAR BOX TYPES** 

& PROPELLER COMBINATIONS

ROTAX TYPE C (REDUCTION 3:1) ROTAX TYPE E (REDUCTION 2.62:1)

AIRBORNE (IVO) - 64 INS. DIA. 15 DEG. PITCH AT TIP

ROTAX TYPE C (REDUCTION 4:1) ROTAX TYPE E (REDUCTION 3.47:1)

BROLGA 4 BLADE - 68 INS DIA. 17 DEG. PITCH

FUEL GRADE:

SUPER GRADE MOTOR SPIRIT

FUEL MIXTURE:

50:1 - TWO-STROKE OIL

AIRSPEED LIMITS:

NEVER EXCEED 54 KIAS

No OF SEATS:

2

MAXIMUM WEIGHT:

401 KG

LOADING:

MINIMUM PILOT WEIGHT 65 KG - THE AIRCRAFT MUST BE FLOWN SOLO FROM THE FRONT SEAT. MAXIMUM OCCUPANT WEIGHT 180 KG - PILOT

AND PASSENGER.

EMPTY TRIKE CG:

WHEN SUSPENDED FROM THE MAST HEAD BOLT THE TRIKE BASE IS INCLINED 5.7 DEGS. NOSE DOWN

MANOEUVRES:

PITCH ANGLES LESS THAN + 45 DEG. FROM THE HORIZONTAL. MAXIMUM BANK ANGLE 60 DEGS. AEROBATICS, SPINS, NEGATIVE G

MANEUVERS, WHIPSTALLS AND STALLED SPIRAL

DESCENTS PROHIBITED.

MANUFACTURERS

TRIKE BASE - E 503X -265 AND UP

SERIAL NUMBERS: WING - W-01 AND UP

NOTE: COMBINATIONS OF ACCEPTED SERIAL NUMBERS ARE PERMITTED.

ACCEPTANCE BASIS:

CIVIL AVIATION ORDER SECTION 95.32 ISSUE 1,

PLUS AIRBORNE WINDSPORTS CAO 95.32 AIRWORTHINESS CONDITIONS DATED MARCH 1990

SIGNED

I. KEARSLEY FOR CASA – 7/8/2002